



MD508 C-RT

Roller Top

Modular Belt Series

- **Packaging Applications**

Labelling, Case Packers, Tray Packers, Palletizing - Depalletizing, Accumulation Lines


- **Bakery Applications**

Pan & Tray Handling

- **Meat&Poultry Applications**

Case & Box Handling, Accumulation Lines

MD508 C-RT (Roller Top)





Pitch:	50,8 mm / 2 inch
Belt Surface:	Close, Smooth Surface
Minimum Width:	150 mm / 5.90 inch
Open Area (%):	0%.
Flight:	Yes
Sidewall:	No
Pin:	Ø 7 mm / 0.275 inch - Self Lock
Approved:	FDA and EU
Color:	Blue / White / Gray
Cleanability:	Good
Belt Thickness:	16 mm / 0.629 inch

MD508 C-RT Technical Information

Belt Material		POM	POM
Roller Material		POM	
Pin Material		PA	POM
Belt Strength	N/m lb/ft	42000 - 2877	42000 - 2877
Temperature	°C °F	-40 / +93 -40 / +200	-40 / +93 -40 / +200
Belt Weight	kg/m² lb/sqft²	13.5 / 2.77	13.5 / 2.77

Diameter of idling rollers (min.)		Diameter of support rollers (min.)		Diameter for gravity take up center drive rollers (min.)		Backbending radius for elevators without side guards or hold down devices (min.)		Backbending radius for elevators with side guards or hold down devices (min.)	
mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
90	3.5	100	4	150	6	150	6	250	10

Belt Width mm	150,0	225,0	300,0	375,0	450,0	525,0	600,0	675,0	750,0	825,0	900,0	975,0	1050,0	1125,0	1200,0	1275,0	1350,0
Belt Width inch	5.91	8.86	11.81	14.76	17.72	20.67	23.62	26.57	29.53	32.48	35.43	38.39	41.34	44.29	47.24	50.20	53.15
Belt Width mm	1425,0	1500,0	1575,0	1650,0	1725,0												
Belt Width inch	56.10	59.06	62.01	64.96	67.91												



Product Features and Functional Benefits

- Closed, Flat top surface.
- High horizontal and vertical strength.
- High load capacity for wide and long conveyors.
- Speeding operations, place the wearstrips under the rollers.
- Accumulation operations, place the wearstrips between rollers.

Important Notes

- Standard belt increments 75 mm.
- Non-standard belt increments 18,75 mm.
- Central distance between rollers and offset to next row up to request.
- Please contact with customer service for precise belt measurements.
- Special raw materials and additional colors available.
- Physical belt widths are generally 0.1% to 0.3% smaller.

MD508 Series

Sprockets and Technical Specifications




Z8



Z10



Z12



MD508 Series / Molded Sprocket Dimensions

NO. TEETH	Di mm/inch	Do mm/inch	A mm/inch	B mm/inch	Square Bore (Q)		Round Bore (R)		PRODUCT CODE	
					mm	inch	mm	inch	Square Type (Q)	Round Type (R)
Z8	107,4 / 4.23	127,4 / 5.01	40,00 / 1.57	7,00 / 0.27	40	1.5	25 to 30	1 to 1.25	MD-TR508SQZ8*POM	MD-TR508SRZ8*POM
Z10	141,3 / 5.56	160,4 / 6.31	40,00 / 1.57	7,00 / 0.27	40	1.5	25 to 30	1 to 1.25	MD-TR508SQZ10*POM	MD-TR508SRZ10*POM
Z12	174,7 / 6.87	193,27 / 7.61	40,00 / 1.57	7,00 / 0.27	40	1.5	25 to 30	1 to 1.25	MD-TR508SQZ12*POM	MD-TR508SRZ12*POM
Z16	240,9 / 9.48	258,7 / 10.18	40,00 / 1.57	7,00 / 0.27	60 & 90	-	-	-	MD-TR508SQZ16*POM	MD-TR508SRZ16*POM

*Other sprockets and hub sizes are manufactured on request..

*PA (Polyamide) sprockets raw material is available on request.


*Machined Split Sprockets are available on request.




Clamp



Machined Split Sprocket



Moulded Sprocket



Machined Sprocket

MD508 Series

Accessories and Technical Specifications

MD508 Series / Flight & Sidewall Dimensions

MD508 Series / Flights & Universal Sidewalls				
PRODUCT CODE	Flight Height (mm/inch)	Flight Width (mm/inch)	PRODUCT CODE	Sidewall Height (mm/inch)
MD508T50	50 / 1.97	150 / 5.9	U508SW50	53 / 2.09
MD508T100	75 / 2.95	150 / 5.9	U508SW75	78 / 3.07
MD508T150	100 / 3.94	150 / 5.9	U508SW100	103 / 4.05




MD508 Series / Standard Installation of Flights and Sidewalls

Possible Sidewall and Flights Indents	Z		X (Max.)		Y (Min.)	
	mm	inch	mm	inch	mm	inch
Standard, module cutting	37,50	1.48	34,15	1.34	17,15	0.68
Standard, module cutting	56,25	2.21	52,90	2.08	35,90	1.41
Standard, module cutting	75,00	2.95	71,65	2.82	54,65	2.15
Standard, module cutting	112,50	4.43	109,15	4.30	92,15	3.63
Standard, module cutting	131,25	5.17	127,9	5.04	110,9	4.37

*X and Y dimensions may change depending on the sidewall height:


X (Max.) tolerance is -2 mm

Y (Min.) tolerance is +2 mm.



MD508 Series

Engineering Information



MD508 Series / Sprocket & Wearstrip Arrangements

Standard Belt Width		Number of sprockets per shaft	Number of wearstrips		A (mm/inch)	
mm	inch		Carryway	Returnway	Min.	Max.
150	5.9	2	2	2	75 / 2.9	150 / 5.9
225	8.9	2	2	2	75 / 2.9	150 / 5.9
300	11.8	2	3	2	75 / 2.9	150 / 5.9
375	14.8	3	3	3	75 / 2.9	150 / 5.9
450	17.7	3	3	3	75 / 2.9	150 / 5.9
525	20.7	3	4	3	75 / 2.9	150 / 5.9
600	23.6	3	4	3	75 / 2.9	150 / 5.9
675	26.6	5	5	3	75 / 2.9	150 / 5.9
750	29.5	5	5	4	75 / 2.9	150 / 5.9
825	32.5	5	6	4	75 / 2.9	150 / 5.9
900	35.4	5	6	4	75 / 2.9	150 / 5.9
975	38.4	7	7	5	75 / 2.9	150 / 5.9
1050	41.3	7	7	5	75 / 2.9	150 / 5.9
1125	44.3	7	7	5	75 / 2.9	150 / 5.9
1200	47.2	7	8	5	75 / 2.9	150 / 5.9
1500	59.0	9	8	6	75 / 2.9	150 / 5.9
1800	70.9	11	9	6	75 / 2.9	150 / 5.9
2100	82.7	13	10	7	75 / 2.9	150 / 5.9
2400	94.5	15	11	9	75 / 2.9	150 / 5.9
2700	106.3	17	12	9	75 / 2.9	150 / 5.9
3000	118.1	19	13	10	75 / 2.9	150 / 5.9

Note:

*The number of sprockets and wearstrips may vary depending on the load.

*For wider belts, central distance of sprockets recommended to be maximum 150mm (5.9").

*For wider belts, central distance of carryway & returnway wearstrips may change 250mm (9.8") to 300mm (11.8").